

Reduce Your Printing Cost At Utmost

Let the new Pantum P3300 series bring your business value with auto-duplex high speed printing for high working efficiency, low paper jam rate for fluent operation, and eco-friendly separate drum unit and toner cartridge to reduce your cost at utmost. It is ideally suited for users no matter from small business group or from large shared workgroup who require affordable running cost.



SILENT PRINTING MODE TO LOWER THE NOISE
AND CREATE A COMFORTABLE OFFICE ENVIRONMENT



One-Step Driver Installation
and Direct Printing



High Print Speed



Convenient
to Print



Office Document Direct
Print from Mobile Devices



Lowpaper Jam Rate
Design for Engine



Separate Drum
and Toner

KEY SPECIFICATIONS



P3300 Series

Monochrome Laser Printer

MODEL

■ P3300DN

■ P3300DW

PRINTING

Print technology	Mono laser		
Print speed	33ppm(A4)/35ppm(Letter)		
First print out time	Less than 8.2 seconds		
Maximum Monthly Duty Cycle	60000 pages		
Recommended monthly volume	750 to 3500 pages		
Processor speed	350 MHz		
Memory	256 MB		
Printer language	PCL5e, PCL6, PS3, PDF		
Duplex mode	Auto		
Control panel	2Line LCD		
NFC print	No	:	Yes
Network print	Yes		
Wireless print	No	:	Yes

PAPER HANDLING

Paper input tray	250 pages		
Multipurpose tray	1 pages		
Paper output tray	150 pages		
Media types	Plain, Thick, Transparency, Cardstock, Label		
Media sizes	A4, A5, JISB5, ISOB5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2		
Media weight	Input tray: 60-105g/m ² Multipurpose tray: 60-200g/m ²		

GENERAL

Dimensions (WxDxH)	354 x 334 x 232mm (13.9 x 13.1 x 9.1in)		
Weight (with toner cartridge)	6.8kg (15lb)		
Operating temperature range	10-32 °C (50-95 °F)		
Operating humidity range	20% - 80% RH		
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%, +10%), 50/60Hz(±2Hz), 4.5A		
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A)		
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2 W		
Operating system compatibility	Microsoft Windows Server 2008/2012/2016/2019/XP/Vista/Win7/Win8/Win8.1/Win10/Win11 Mac OS 10.10/10.11/10.12/10.13/10.14/10.15/11.0/11.1/11.2/11.3/11.4/11.5/11.6/12 Linux (Ubuntu12.04&14.04&16.04&18.04&20.04&22.04)		
Interface	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	:	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

SUPPLIES

Cartridge style	Separate drum and toner		
Starter cartridge capacity ⁽¹⁾	TL-410 (1500 pages)		
Cartridge and drum capacity ⁽¹⁾	Cartridge: TL-410 (1500 pages, Standard); TL-410H (3000 pages, High); TL-410X (6000 pages, Extra high) Drum: DL-410 (12000pages)		
Starter drum unit lifetime ⁽¹⁾	DL-410 (12000 pages)		

WHAT'S IN THE BOX

Printer × 1 / 1500 Page Toner Cartridge × 1 / 12000 Page Drum unit × 1 / USB Interface Cable × 1 /
Power Cord × 1 / CD-ROM × 1 / Quick Setup Guide × 1

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)
Copyright © 2020 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.
*Printer data based on Pantum internal testing.